REPORT ON
SEQUENCE IIIG EVALUATION

VERSION *20021210*

CONDUCTED FOR

TSTSPON1
TSTSPON2

LABVALID	V = VALID
	I = INVALID
	N = RESULTS CANNOT BE INTERPRETED AS REPRESENTATIVE OF OIL PERFORMANCE (NON-REFERENCE OIL) AND SHALL NOT BE USED FOR MULTIPLE TEST ACCEPTANCE

TSTOIL	NR = Non-Reference Oil Test
	RO = Reference Oil Test

Test Number					
Test Stand	*STAND*	Stand Test Number	*STRUN*	Lab Test Number	*LABRUN*
Oil Code	*OILCODE*				
Formulation/Stand Code	*FORM*				
Alternate Codes	*ALTCODE1*	*ALTCODE2*	*ALTCODE3*		
EOT Date	*DTCOMP*	EOT Time	*EOTTIME*		

In my opinion this test *OPVALID* been conducted in a valid manner in accordance with the latest draft of Sequence IIIG procedure and the appropriate amendments through the information letter system. The remarks included in the report describe the anomalies associated with this test.

SUBMITTED BY: *SUBLAB*

Testing Laboratory

SUBSIGIM

Signature

SUBNAME

Typed Name

SUBTITLE

Title

Form 2

Sequence IIIG

Table of Contents

1.	Title / Validity Declaration Page	Form 1
2.	Table of Contents	Form 2
3.	Summary of Test Method	Form 3
4.	Test Result Summary	Form 4
5.	Operational Summary	Form 5
6.	Used Oil Analysis	Form 6
7.	Valve Lifter and Camshaft Wear Results	Form 7
8.	Summary of Oil Ring Land Deposit Rating	Form 8
9.	Summary of Piston Deposits	Form 9
10.	Blowby Values & Plot	Form 10
11.	Viscosity Increase Plot	Form 11
12.	Hardware Information	Form 12
13.	Downtime & Outlier Report Form	Form 13

Sequence IIIG

FORM 3

Summary of Test Method

The Sequence IIIG Test is a fired-engine, dynamometer lubricant test for evaluating automotive engine oils for certain high-temperature performance characteristics, including oil thickening, varnish deposition, oil consumption, and engine wear. Such oils include both single viscosity grade and multiviscosity grade oils that are used in spark-ignition, gasoline-fueled engines, as well as diesel engines.

The Sequence IIIG Test utilizes a 1996 model General Motors 3800 Series II, water-cooled, 4 cycle, V-6 engine as the test apparatus. The Sequence IIIG test engine is an overhead valve design (OHV) and uses a single camshaft operating both intake and exhaust valves via pushrods and hydraulic valve lifters in a sliding-follower arrangement. The engine uses one intake and one exhaust valve per cylinder. Induction is handled by a modified GM port fuel injection system setting the Air-to-Fuel ratio at 15:1. The test engine is overhauled prior to each test, during which critical engine dimensions are measured and rated or measured parts (pistons, camshaft, valve lifters, etc.) are replaced.

The Sequence IIIG Test consists of a 10-minute operational check, followed by 100 hours of engine operation at moderately high speed, load, and temperature conditions. The 100-hour segment is broken down into five 20-hour test segments. Following each 20-hour segment, and the 10-minute operational check, oil samples are drawn from the engine. The kinematic viscosities of the 20-hour segment samples are compared to the viscosity of the 10-minute sample to determine the viscosity increase of the test oil.

The Sequence IIIG Test is operated at the following test states during the 100-hour portion of the test:

Parameter	Set Point
Engine Speed	3600 r/min
Engine Load	250 N-m
Oil Filter Block Temperature	150 ˚C
Coolant Outlet Temperature	115 ˚C
Fuel Pressure	365 kPa
Intake Air Temperature	35 ˚C
Intake Air Pressure	0.05 kPa
Intake Air Dew Point	16.1 ˚C
Exhaust Back Pressure	6 kPa
Engine Coolant Flow	160 L/min
Breather Tube Coolant Flow	10 L/min
Air-to-Fuel Ratio	15.0:1
Breather Tube Coolant Outlet Temperature	40 ˚C

SEQUENCE IIIG
FORM 4
TEST RESULT SUMMARY

LAB	*LAB*	OIL CODE	*OILCODE*
TEST STAND NO.	*STAND*	TEST NO.	*STAND - STRUN - LABRUN*
LABORATORY OIL CODE	*LABOCODE*		
FORMULATION STAND CODE	*FORM*		

DATE STARTED	*DTSTRT*	ENGINE NO.	*ENGINENO*
TIME STARTED	*STRTTIME*	FUEL BATCH	*FUELBTID*
DATE COMPLETED	*DTCOMP*	SAE VISCOSITY	*SAEVISC*
TIME COMPLETED	*EOTTIME*	TMC OIL CODE [A]	*IND*
TEST LENGTH	*TESTLEN*		

Pass/Fail Results						
	Viscosity Increase (%)	Average Cam + Lifter Wear (µm)	Average Weighted Piston Deposits (merits)	Average Piston Skirt Varnish (merits)	Number of Hot-Stuck Rings	Oil Consumption (L) [B]
Original Units	*PVIS*	*ACLW*	*WPD*	*APV*	*HSTUKT*	*OILCON*
Transformed Results	*TPVIS*	*TACLW*				
Industry Correction Factor	*PVIS_CF*	*ACLW_CF*	*WPD_CF*	*APV_CF*		
Corrected Transformed Result	*PVIS_COR*	*ACLW_COR*				
Severity Adjustment	*PVIS_SA*	*ACLW_SA*	*WPD_SA*	*APV_SA*		
Final Transformed Result	*TPVISFNL*	*TACLWFNL*				
Final Original Unit Result	*PVISFNL*	*ACLWFNL*	*WPDFNL*	*APVFNL*		

Additional Results			
Oil Consumption Hours, h [B]	*OCONHRS*	Average Oil Ring Plugging , %	*ORPAVG*
Maximum Cam + Lifter Wear, µm	*MCLW*	Number of Cold-Stuck Rings	*CSTUKT*

Most Recent Stand Reference Oil Test History [C]			
Test Number	*RSTAND - RSTRUN - RLABRUN*		
Oilcode	*ROILCODE*		
Date Completed	*RDTCOMP*	TMC Oil Code	*RIND*
Final Viscosity Increase, %	*RPVISFNL*	Fuel Batch	*RFUELBID*
Final Average Piston Skirt Varnish, merits	*RAPVFNL*		
Final Average Cam + Lifter Wear, µm	*RACLWFNL*		
Final Maximum Cam + Lifter Wear, µm	*RMCLWFNL*		
Final Average Weighted Piston Deposit, merits	*RWPDFNL*		

[A] Reference Oil Tests Only

[B] Test Hours at which Oil Consumption was calculated

[C] Non-Reference Oil Tests Only

SEQUENCE IIIG
FORM 5
OPERATIONAL SUMMARY

LAB	*LAB*	OIL CODE	*OILCODE*
TEST STAND NO.	*STAND*	TEST NO.	*STAND - STRUN - LABRUN*
LABORATORY OIL CODE	*LABOCODE*		
FORMULATION STAND CODE	*FORM*		

	Parameter	Units	QI Threshold	EOT QI	Target	Average	Standard Deviation	Number Of	
								Samples	BQD
Controlled Parameters	Speed	r/min	0.000	*QRPM*	3600	*ARPM*	*SRPM*	*NRPM*	*BRPM*
	Load	Nm	0.000	*QLOAD*	250	*ALOAD*	*SLOAD*	*NLOAD*	*BLOAD*
	Oil Filter Block	˚C	0.000	*QOTEMP*	150.0	*AOTEMP*	*SOTEMP*	*NOTEMP*	*BOTEMP*
	Engine Coolant Out	˚C	0.000	*QCOLOUT*	115.0	*ACOLOUT*	*SCOLOUT*	*NCOLOUT*	*BCOLOUT*
	Condenser Coolant Out	˚C	0.000	*QCCOLOUT*	40.0	*ACCOLOUT*	*SCCOLOUT*	*NCCOLOUT*	*BCCOLOUT*
	Left Air-to-Fuel Ratio		0.000	*QLAFR*	15.0	*ALAFR*	*SLAFR*	*NLAFR*	*BLAFR*
	Right Air-to-Fuel Ratio		0.000	*QRAFR*	15.0	*ARAFR*	*SRAFR*	*NRAFR*	*BRAFR*
	Left Exhaust Back Pressure	kPa	0.000	*QLEXBP*	6.0	*ALEXBP*	*SLEXBP*	*NLEXBP*	*BLEXBP*
	Right Exhaust Back Pressure	kPa	0.000	*QREXBP*	6.0	*AREXBP*	*SREXBP*	*NREXBP*	*BREXBP*
	Intake Air	kPa	0.000	*QINAIR*	0.05	*AINAIR*	*SINAIR*	*NINAIR*	*BINAIR*
	Engine Coolant Flow	L/min	0.000	*QCOLFLO*	160.0	*ACOLFLO*	*SCOLFLO*	*NCOLFLO*	*BCOLFLO*

	Parameter	Units	Average	Standard Deviation	Number Of	
					Samples	BQD
Non-controlled Parameters	Oil Sump	˚C	*AOSUMP*	*SOSUMP*	*NOSUMP*	*BOSUMP*
	Pump Outlet Pressure	kPa	*APOUTP*	*SPOUTP*	*NPOUTP*	*BPOUTP*
	Gallery Pressure	kPa	*AOILPRS*	*SOILPRS*	*NOILPRS*	*BOILPRS*
	Engine Coolant In	˚C	*AECOLIN*	*SECOLIN*	*NECOLIN*	*BECOLIN*
	Fuel Inlet	˚C	*AFUELIN*	*SFUELIN*	*NFUELIN*	*BFUELIN*
	Intake Air	˚C	*AINAT*	*SINAT*	*NINAT*	*BINAT*
	Intake Air Dew Point	˚C	*AINDEW*	*SINDEW*	*NINDEW*	*BINDEW*
	Intake Vacuum	kPa	*AINVAC*	*SINVAC*	*NINVAC*	*BINVAC*
	Crankcase	kPa	*ACCASEP*	*SCCASEP*	*NCCASEP*	*BCCASEP*
	Fuel Pressure	kPa	*APFUEL*	*SPFUEL*	*NPFUEL*	*BPFUEL*

OIL CONSUMPTION DATA						
HOURS	Initial Run-in	*OCONH020*	*OCONH040*	*OCONH060*	*OCONH080*	*OCONH100*
LEVEL (ml) low	*OILLINI*	*OILLH020*	*OILLH040*	*OILLH060*	*OILLH080*	*OILLH100*

NO_x Measurement			
Hours	*NOXHH019*	*NOXHH049*	*NOXHH099*
NO_x, ppm	*NOX_H019*	*NOX_H049*	*NOX_H099*

SEQUENCE IIIG
FORM 6
USED OIL ANALYSIS RESULTS

LAB	*LAB*	OIL CODE	*OILCODE*
TEST STAND NO.	*STAND*	TEST NO.	*STAND - STRUN - LABRUN*
LABORATORY OIL CODE	*LABOCODE*		
FORMULATION STAND CODE	*FORM*		

VISCOSITY INCREASE DATA (cSt AT 40˚C)			
HOURS	VISCOSITY [A]	CHANGE	PERCENT
NEW OIL	*VNEW*		
INITIAL [B]	*VINI*		
VISTH020	*VIS_H020*	*DVISH020*	*PVISH020*
VISTH040	*VIS_H040*	*DVISH040*	*PVISH040*
VISTH060	*VIS_H060*	*DVISH060*	*PVISH060*
VISTH080	*VIS_H080*	*DVISH080*	*PVISH080*
VISTH100	*VIS_H100*	*DVISH100*	*PVISH100*
TESTLEN	*VISEOT*	*DVISEOT*	*PVIS*

[A] 8000 cSt is maximum allowable viscosity

[B] At end of leveling run

Results of ICP Analysis of Used Oil			
Hours	Iron	Copper	Lead
Initial	*FEWMINI*	*CUWMINI*	*PBWMINI*
TST_H020	*FEWMH020*	*CUWMH020*	*PBWMH020*
TST_H040	*FEWMH040*	*CUWMH040*	*PBWMH040*
TST_H060	*FEWMH060*	*CUWMH060*	*PBWMH060*
TST_H080	*FEWMH080*	*CUWMH080*	*PBWMH080*
TST_H100	*FEWMH100*	*CUWMH100*	*PBWMH100*
TESTLEN	*FEWMEOT*	*CUWMEOT*	*PBWMEOT*

Cold Crank Simulator Results, D 5293	
Specified Temperature, ˚C	*CCSTEMP*
Cold-Crank Simulator Viscosity at Specifield Temperature, cP	*CCS*
Second Temperatue, ˚C	*CCSTEMP2*
Cold-Crank Simulator Viscosity at Second Temperature, cP	*CCS2*

Mini-Rotary Viscometer Results, D 4684	
MRV Temperature, ˚C	*MRVTEMP*
MRV Result, cP	*MRV*
Yield Stress, cP	*YSTRESS*

SEQUENCE IIIG
FORM 7
VALVE LIFTER AND CAMSHAFT WEAR RESULTS

LAB	*LAB*	OIL CODE	*OILCODE*
TEST STAND NO.	*STAND*	TEST NO.	*STAND - STRUN - LABRUN*
LABORATORY OIL CODE	*LABOCODE*		
FORMULATION STAND CODE	*FORM*		

NUMBER	CAMSHAFT LOBE, µm	VALVE LIFTER, µm	CAM & LIFTER WEAR, µm
1	*CAMW01*	*LFTW01*	*CLW01*
2	*CAMW02*	*LFTW02*	*CLW02*
3	*CAMW03*	*LFTW03*	*CLW03*
4	*CAMW04*	*LFTW04*	*CLW04*
5	*CAMW05*	*LFTW05*	*CLW05*
6	*CAMW06*	*LFTW06*	*CLW06*
7	*CAMW07*	*LFTW07*	*CLW07*
8	*CAMW08*	*LFTW08*	*CLW08*
9	*CAMW09*	*LFTW09*	*CLW09*
10	*CAMW10*	*LFTW10*	*CLW10*
11	*CAMW11*	*LFTW11*	*CLW11*
12	*CAMW12*	*LFTW12*	*CLW12*
MAXIMUM	*MAXCW*	*MAXLFTW*	*MCLW*
MINIMUM	*MINCW*	*MINLFTW*	*MINCLW*
AVERAGE	*AVGCW*	*AVGLFTW*	*ACLW*

SEQUENCE IIIG
FORM 8
SUMMARY OF OIL RING LAND DEPOSIT RATING

LAB	*LAB*	OIL CODE	*OILCODE*
TEST STAND NO.	*STAND*	TEST NO.	*STAND - STRUN - LABRUN*
LABORATORY OIL CODE	*LABOCODE*		
FORMULATION STAND CODE	*FORM*		
RATER	*RLDRATER*	RATING DATE	*RLDRTDT*

PISTON	OIL RING LAND DEPOSIT, MERITS	% CHIPPED
1	*ORLD1*	*ORCHIP1*
2	*ORLD2*	*ORCHIP2*
3	*ORLD3*	*ORCHIP3*
4	*ORLD4*	*ORCHIP4*
5	*ORLD5*	*ORCHIP5*
6	*ORLD6*	*ORCHIP6*
Average	*ORLD*	*AVGORCHP*

PISTON	% OIL RING PLUGGING	RING STICKING [A]	
		HOT-STUCK RINGS	COLD-STUCK RINGS
1	*ORP1*	*HSTUK1*	*CSTUK1*
2	*ORP2*	*HSTUK2*	*CSTUK2*
3	*ORP3*	*HSTUK3*	*CSTUK3*
4	*ORP4*	*HSTUK4*	*CSTUK4*
5	*ORP5*	*HSTUK5*	*CSTUK5*
6	*ORP6*	*HSTUK6*	*CSTUK6*
Total		*HSTUKT*	*CSTUKT*
Average	*ORPAVG*		

[A] Possible values T = top compression ring
B = bottom compression ring
O = oil ring
N = none

SEQUENCE IIIG
FORM 9
SUMMARY OF PISTON DEPOSITS

LAB	*LAB*	OIL CODE	*OILCODE*
TEST STAND NO.	*STAND*	TEST NO.	*STAND - STRUN - LABRUN*
LABORATORY OIL CODE	*LABOCODE*		
FORMULATION STAND CODE	*FORM*		
RATER	*APVRATER*	RATING DATE	*APVRTDT*

NOTE: CRC Manual 14 used for ALL Ratings

NOTE: These are unweighted ratings.

	Grooves, merits			Lands, merits		Undercrown, merits
	1	2	3	2	3	
Piston 1	*G1P1*	*G2P1*	*G3P1*		*ORLD1*	
Piston 2					*ORLD2*	
Piston 3					*ORLD3*	
Piston 4					*ORLD4*	
Piston 5					*ORLD5*	
Piston 6					*ORLD6*	
WF	0.05	0.10	0.20	0.15	0.30	0.10

NOTE: These are unweighted ratings.

	Piston Skirt Varnish, merits		
	Thrust	Anti-Thrust	Average
Piston 1			
Piston 2			
Piston 3			
Piston 4			
Piston 5			
Piston 6			
Average			*APV*
WF			0.10

PSVAVx = (PSVTx + PSVAx)/2 *where x = Number of Piston*
PSVTAV = average of six Thrust Piston Skirt ratings.
PSVAAV = average of six Anti-Thrust Piston Skirt ratings.
APV = average of all 12 Piston Skirt ratings.

	Total Weighted Deposits, merits
Piston 1	
Piston 2	
Piston 3	
Piston 4	
Piston 5	
Piston 6	

WPDx=(WF*G1Px)+(WF*G2Px)+(WF*G3Px)+(WF*L2Px)+
(WF*ORLDx)+(WF*UCPx)+(WF*PSVAVx)
where: x=Number of Piston
WF=Appropriate Weighting Factor (WF) for part, from table.

Average Weighted Piston Deposits, merits	*WPD*

WPD=(WPD1+WPD2+WPD3+WPD4+WPD5+WPD6)/6

SEQUENCE IIIG
FORM 10
BLOWBY VALUES & PLOT

LAB	*LAB*	OIL CODE	*OILCODE*
TEST STAND NO.	*STAND*	TEST NO.	*STAND - STRUN - LABRUN*
LABORATORY OIL CODE	*LABOCODE*		
FORMULATION STAND CODE	*FORM*		

Blowby Plot

Test Hours										
Blowby, L/min.										
Test Hours										
Blowby, L/min.										

Test Hours		Average
Blowby, L/min.		

SEQUENCE IIIG
FORM 11
VISCOSITY INCREASE PLOT

LAB	*LAB*	OIL CODE	*OILCODE*
TEST STAND NO.	*STAND*	TEST NO.	*STAND - STRUN - LABRUN*
LABORATORY OIL CODE	*LABOCODE*		
FORMULATION STAND CODE	*FORM*		

SEQUENCE IIIG
FORM 12
HARDWARE INFORMATION

LAB	*LAB*	OIL CODE	*OILCODE*
TEST STAND NO.	*STAND*	TEST NO.	*STAND - STRUN - LABRUN*
LABORATORY OIL CODE	*LABOCODE*		
FORMULATION STAND CODE	*FORM*		

Build Completion Date		Piston Batch (Code)		
Block Serial Number		Piston Size (Grade)		
Crankshaft Serial Number		Piston Ring Batch Code		
Camshaft Serial Number		Oil Filter Batch Code		
Cylinder Head Serial Number, Left		Intake Valve Seals Batch Code		
Cylinder Head Serial Number, Right		Valve Springs Batch Code		
Bearing Kit Serial Number		Lifter Serial Number	1	
Top Ring Gap, mils			2	
Bottom Ring Gap, mils			3	
			4	
			5	
			6	
			7	
			8	
			9	
			10	
			11	
			12	

SEQUENCE IIIG
FORM 13
DOWNTIME & OUTLIER REPORT FORM

LAB	*LAB*	OIL CODE	*OILCODE*
TEST STAND NO.	*STAND*	TEST NO.	*STAND - STRUN - LABRUN*
LABORATORY OIL CODE	*LABOCODE*		
FORMULATION STAND CODE	*FORM*		

Downtime Occurrences	

Test Hours	Date	Total Downtime	Reasons
Total Downtime			Maximum allowable downtime: 24 hours

Other Comments & Outliers	