



Test Monitoring Center

@ Carnegie Mellon University
6555 Penn Avenue, Pittsburgh, PA 15206, USA

<http://astmtmc.cmu.edu>
412-365-1000

D4485 Information Letter 19-3
Sequence Number 3
August 15, 2019

ASTM consensus has not been obtained on this information letter. An appropriate ASTM ballot will be issued in order to achieve such consensus.

TO: D4485 Mailing List

SUBJECT: ASTM D7094 added to "S" Category Bench Test Requirements

On July 9, 2019 the D4485 Surveillance Panel approved changes to D4485-18a to add test method D7094 Standard Test Method for Flash Point by Modified Continuously Closed Cup (MCCCFP) as an approved test method to the "S" Category Bench Test requirements. The changes are detailed below.

1. Add D7094, Standard Test Method for Flash Point by Modified Continuously Closed Cup (MCCCFP) to D4485 Referenced Documents section 2.
2. Add D7094 with foot note "v" to "S" Category Tables

The text of the revision is shown in the attachment. This change is effective with the issuance of this information letter.

Joe Franklin
Chairman
ASTM Subcommittee B

Frank M. Farber
Director
ASTM Test Monitoring Center

Attachment

c: http://www.astmtmc.cmu.edu/ftp/docs/d4485/IL_19-3_D4485.pdf

Distribution: Email

Revises D4485-18a

Add to section 2. Referenced Documents

D7094 Standard Test Method for Flash Point by Modified Continuously Closed Cup (MCCCFP) Tester

Add D7094 to “S” Category tables with foot note “v”

Test Method D92 flash point, °C, min ^v	200	NR ^U
Test Method D93 , or D7094 flash point, °C, min ^v	185	NR ^U

^v Meet either Test Methods **D92**, **D93**, or **D7094** flash point requirement.