PC-9 Matrix Design Task Force

Status Report

To

ASTM Heavy Duty
Engine Oil Classification Panel
December 5, 2000

(Modified to address Changes Requested by the HDEOCP on November 2, 2000)

Final Formulations Matrix (9 Test Oils)

Code	Technology	Base Oil	Featured Oil for This Test
PC-9A	×	1	T-10/EGR
PC-9B	×	2	
PC-9C	×	3	
PC-9D	Y	1	
PC-9E	Y	2	M11/EGR
PC-9F	Y	3	
PC-9G	Z	1	
PC-9H	Z	2	
PC-9J	Z	3	1Q/EGR

Final Experimental Test Matrix Designs (The Movie*)

PC-9 Matrix Design Task Force

Revised -- November 10, 2000

I. Assumptions

- o 3 DI/VI combinations, 3 base oils, and 1 Featured Oil/Test type
- o Every factor level should be run at least 3 times to maintain Power, and at least 4 valid test results in each Matrix stand to account for bias
- o At least 8 degrees of freedom (DF) to estimate test variability, and at least 6 repeats on identified Featured Oils
- o Main effects and 2-Way Interactions (Except with Stand) are estimable
- o Independent Labs must run the majority of the Featured Oils (HDEOCP)
- o Dependent Labs are Limited to 4 runs per stand (HDEOCP)
- o Featured Oils should be run first in the Matrix (HDEOCP)
- o Decision rules for Industry Matrix Testing have been satisfied

ATTACHMENT 5, 5 OF

PC-9 Matrix Design Task Force Update

II. Experimental Test Matrix Design Oils

Nine Matrix Oils are Formulated (Blended Lubricants)

	Technology			
Base Oil	X	Υ	Z	
1	PC-9A	PC-9D	PC-9G	
2	PC-9B	PC-9E	PC-9H	
3	PC-9C	PC-9F	PC-9J	

Note:

PC-9A is the Featured Oil for the T-10/EGR, PC-9E is the Featured Oil for the M11/EGR,

PC-9J is the Featured Oil for the 1Q/EGR.

III. T-10/ EGR Test Design

Lab/ Stand						
La	b 1	Lab 2	La	b 3	Lab 4	Lab 5
1	2	3	4	5	6	7
A	A	A	A	A	A	A
G	A	G	D	A	A	D
Е	Е	В	Н	Е	Н	В
С	J	F	С	J	F	J

IV. M11/ EGR Test Design

Lab/ Stand						
Lab 1		Lab 2	Lab 3		Lab 4	
1	2	3	4	5	6	
Е	Е	Е	Е	Е	E	
Н	Е	Н	В	Е	В	
A	G	D	G	A	D	
F	С	С	F	J	J	
Е			Е			

V. 1Q/EGR Test Design

Lab/ Stand						
La	b 1	Lab 2	La	b 3	Lab 4	Lab 5
1	2	3	4	5	6	7
J	J	J	J	J	J	J
С	J	С	F	J	J	F
Е	E	Н	В	Е	В	Н
G	A	D	G	A	D	A

VI. NOTES

- o The Featured Oil is run 10 Times in every Test
- o Each Stand Tests every Base Oil and Technology

Proposed Timeline:

- PC-9 Formulations Matrix
 - Technologies Selected April 11, 2000
 - Technologies Available September 7, 2000
 - Base Oils Available October 10, 2000
 - Blends Prepared (Available) November 27, 2000
- PC-9 Matrix Testing
 - Matrix Start December 2000
 - Matrix CompletionMarch 2001
 - Data Evaluation CompletedApril 30, 2001