



A Program of ASTM International

# **Test Monitoring Center**

<http://astmtmc.cmu.edu>

## **ASTM D02.B1 Semiannual Report Passenger Car Reference Oil Testing**

**October 2018**

# Table of Contents

| Section                    | Topic   |
|----------------------------|---|
| Executive Summary          | <a href="#"><u>Summary Items</u></a>              |
| Test Area Status Summaries | <a href="#"><u>Calibrated Labs and Stands</u></a> |
|                            | <a href="#"><u>Seq. IIIF</u></a>                  |
|                            | <a href="#"><u>Seq. IIIG</u></a>                  |
|                            | <a href="#"><u>Seq. IIIH</u></a>                  |
|                            | <a href="#"><u>Seq. IVA</u></a>                   |
|                            | <a href="#"><u>Seq. IVB</u></a>                   |
|                            | <a href="#"><u>Seq. VG</u></a>                    |

# Table of Contents

| Section                    | Topic                            |
|----------------------------|----------------------------------|
| Test Area Status Summaries | (cont.)                          |
|                            | <a href="#"><u>Seq. VH</u></a>   |
|                            | <a href="#"><u>Seq. VIE</u></a>  |
|                            | <a href="#"><u>Seq. VIF</u></a>  |
|                            | <a href="#"><u>Seq. VIII</u></a> |
|                            | <a href="#"><u>Seq. IX</u></a>   |
|                            | <a href="#"><u>Seq. X</u></a>    |

# Table of Contents

| Section                | Topic   |
|------------------------|---|
| Additional Information | <a href="#"><u>Information Letters</u></a>      |
|                        | <a href="#"><u>Reference Oil Inventory</u></a>  |
|                        | <a href="#"><u>LTMS Deviations</u></a>          |
|                        | <a href="#"><u>Quality Index Deviations</u></a> |
|                        | <a href="#"><u>TMC Laboratory Visits</u></a>    |
|                        | <a href="#"><u>Test Area Time Lines</u></a>     |
|                        | <a href="#"><u>Rating Workshop Data</u></a>     |
|                        | <a href="#"><u>Misc. Information</u></a>        |

# Passenger Car Engine Oil Testing

## Executive Summary

- ▶ Seq. IVB
  - Monitoring of the Test began in May.
- ▶ Seq. VH
  - Testing completed on Fuel Batch GI0321NX10. Surveillance panel approved for use on 10/9/18
- ▶ BOI–VGRA
  - Testing is complete for Sequence IIIH, VIE, VIF, IX, and X
  - Testing is underway for VH.

[Return to Table of Contents](#)

# Calibrated Labs and Stands\*

| Test     | Labs | Stands |
|----------|------|--------|
| IIIF     | 2    | 2      |
| IIIG/A/B | 1    | 1      |
| IIIH/A/B | 5    | 17     |
| IVA      | 2    | 2      |
| IVB      | 4    | 8      |
| VG       | 1    | 1      |

[Return to Table of Contents](#)

\*As of 9/30/2018

*Test Monitoring Center*  
<http://astmtmc.cmu.edu>



A Program of ASTM International

# Calibrated Labs and Stands\*

| Test | Labs | Stands |
|------|------|--------|
| VH   | 4    | 10     |
| VIE  | 4    | 15     |
| VIF  | 2    | 7      |
| VIII | 2    | 4      |
| IX   | 3    | 5      |
| X    | 3    | 6      |

[Return to Table of Contents](#)

\*As of 9/30/2018

*Test Monitoring Center*  
<http://astmtmc.cmu.edu>



A Program of ASTM International

# Sequence IIIF

» October 2018

# Sequence IIIF Activity

| Test Status                                 | Validity Code | # |
|---|---------------|---|
| Acceptable Calibration Test                 | AC            | 3 |
| Statistically Unacceptable Calibration Test | OC            | 2 |
| Total                                       |               | 5 |

# Sequence IIIF – Failed Tests

| Test Status  | #        |
|--|----------|
| Mild APV   | 1        |
| Hours to 275% Vis Increase Precision<br>Shewhart Alarm | 1        |
| <b>Totals</b>  | <b>2</b> |


# Sequence IIIF Test Severity

- APV
  - In severity action alarm, mild
  - Long-term mild trend continuing (Since October 2006)
- Hours to 275% Vis Increase
  - In control
- WPD
  - In severity warning alarm (severe)
- PV60
  - In severity action alarm (severe)

# SEQUENCE IIIF INDUSTRY OPERATIONALLY VALID DATA



## AVERAGE PISTON SKIRT VARNISH FINAL ORIG UNIT RES



Test Monitoring Center


<http://astmtmc.cmu.edu>




A Program of ASTM International

## HOURS FINAL ORIG RES (REFERENCE TESTS ONLY)


LTMS Severity Analysis



LTMS Precision Analysis



CUSUM Severity Analysis




# SEQUENCE IIIF INDUSTRY OPERATIONALLY VALID DATA




## AVERAGE WEIGHTED PISTON DEPOSITS FNL ORIG UNIT RES


LTMS Severity Analysis



LTMS Precision Analysis



CUSUM Severity Analysis




Test Monitoring Center


<http://astmtmc.cmu.edu>




A Program of ASTM International

**% VISCOSITY INCREASE @ 060 HOURS**  
 LTMS Severity Analysis


## LTMS Precision Analysis




## CUSUM Severity Analysis




# IIIF Precision Estimates

WPD




# IIIF Precision Estimates

APV




# IIIF Precision Estimates

## PV60



# IIIF Precision Estimates

Hours to 275%



[Return to Table of Contents](#)

# Sequence IIIG/A/B

» October 2018

# Sequence IIIG Activity

| Test Status                 | Validity Code | # |
|-----------------------------|---------------|---|
| Acceptable Calibration Test | AC            | 1 |
| Total                       |               | 1 |

# Sequence IIIG Test Severity

- ACLW in precision warning alarm
  - Long-term mild trend
- PVIS
  - Precision action alarm
  - Severity action alarm (severe)
- WPD in severity warning alarm
  - Long-term severe trend continuing
- MRV is in severity action alarm (severe)
  - Long-term severe trend continuing
- PHOS in control
- Precision plots not updated, only 1 test reported


# SEQUENCE IIIG INDUSTRY OPERATIONALLY VALID DATA




A Program of ASTM International

## AVERAGE CAM + LIFTER WEAR

LTMS Severity Analysis



LTMS Precision Analysis



CUSUM Severity Analysis



**Test Monitoring Center**

<http://astmtmc.cmu.edu>




A Program of ASTM International


## VISCOSE INCREASE

LTMS Severity Analysis


Standard Deviation Units



Standard Deviation Units



Standard Deviation Units



Test Monitoring Center

<http://astmtmc.cmu.edu>

A Program of ASTM International


# SEQUENCE IIIG INDUSTRY OPERATIONALLY VALID DATA




A Program of ASTM International

## AVERAGE WEIGHTED PISTON DEPOSITS


LTMS Severity Analysis



LTMS Precision Analysis



CUSUM Severity Analysis



Test Monitoring Center


<http://astmtmc.cmu.edu>




A Program of ASTM International

## PHOS RETENTION


LTMS Severity Analysis



LTMS Precision Analysis



CUSUM Severity Analysis




Test Monitoring Center


<http://astmtmc.cmu.edu>

## MRV VISCOSITY RESULT

Standard Deviation Units




Standard Deviation Units




Test Monitoring Center

<http://astmtmc.cmu.edu>

# III G Precision Estimates




# IIIG Precision Estimates



# IIIG Precision Estimates

## Phos



Precision estimates for Oct -18 not calculated as only one test reported this period

[Return to Table of Contents](#)

# Sequence IIIH/A/B

» October 2018

# Sequence IIIH Activity

| Test Status  | Validity Code | #         |
|--|---------------|-----------|
| Acceptable Calibration Test                            | AC            | 21        |
| Statistically Unacceptable Calibration Test            | OC            | 3         |
| Pending Calibration Test, Reference Oil 434-3 Targets  | PC            | 1         |
| Aborted Industry Support Test (BOI-VGRA, 70 Hour IIIH) | XI            | 2         |
| BOI-VGRA Matrix Tests, 70 hour IIIH Tests              | NI            | 14        |
| <b>Total</b>   |               | <b>41</b> |

# Sequence IIIH – Failed Tests

| Test Status                     | #        |
|---------------------------------|----------|
| Level 3 Ei Alarm PVIS, MRV, WPD | 1        |
| Level 3 Ei Alarm PVIS, MRV      | 1        |
| Level 3 Ei Alarm PVIS           | 1        |
| <b>Totals</b>                   | <b>3</b> |

# Sequence IIIH - Lost Tests\*


| Test Status | Cause                           | # |
|-------------|---------------------------------|---|
| Aborted     | Unable to maintain oil pressure | 1 |
| Aborted     | High oil consumption            | 1 |
| Totals      |                                 | 2 |

\*Invalid and aborted tests

# Sequence IIIH Test Severity

- All parameters are in control


## VISCOSEITY INCREASE FINAL ORIG UNIT RES




Test Monitoring Center

<http://astmtmc.cmu.edu>


Standard Deviation Units




Standard Deviation Units




Standard Deviation Units




Standard Deviation Units




## PHOSPHORUS RETENTION, FINAL RESULT



# IIIH Precision Estimates



# IIIHA/B Precision Estimates



[Return to Table of Contents](#)

# Sequence IVA

» October 2018

# Sequence IVA Activity

| Test Status                              | Validity Code | #        |
|--|---------------|----------|
| Acceptable Calibration Test              | AC            | 2        |
| Operationally Invalid, Lab determination | LC            | 1        |
| <b>Total</b>                             |               | <b>3</b> |

# Sequence IVA - Lost Tests\*

| Test Status | Cause    | # |
|-------------|----------|---|
| Invalid     | MAP Leak | 1 |
| Totals      |          | 1 |

\*Invalid and aborted tests

# Sequence IVA Test Severity


- ACW in control.

## AVERAGE CAM WEAR


LTMS Severity Analysis



LTMS Precision Analysis



CUSUM Severity Analysis




Test Monitoring Center

<http://astmtmc.cmu.edu>

# Sequence IVA Precision Estimates

ACW



Precision estimates for Oct -18 based on two test results

[Return to Table of Contents](#)

# Sequence IVB

» October 2018

# Sequence IVB Activity

| Test Status   | Validity Code | #         |
|---|---------------|-----------|
| Acceptable Calibration Test                           | AC            | 10        |
| Operationally Invalid, Lab determination              | LC            | 2         |
| Acceptable Donated Test (Keyence Round Robin Lifters) | AG            | 1         |
| Industry Support Test (Engine Life)                   | NI            | 1         |
| <b>Total</b>  |               | <b>14</b> |

# Sequence IVB – Lost Tests\*

| Test Status | Cause  | # |
|-------------|--|---|
| Invalid     | Lobe Failure   | 1 |
| Invalid     | Temperature Calibration Error, Oil Gallery Temperature | 1 |
| Totals      |  | 2 |


\*Invalid and aborted tests

# Sequence IVB Test Severity


- AVLI in control.

## AVERAGE VOLUME LOSS BY KEYENCE BUCKET LIFTER, INTAKE

Standard Deviation Units




Standard Deviation Units



# Sequence IVB Precision Estimates

AVLI



[Return to Table of Contents](#)

# Sequence VG

» October 2018

# Sequence VG Activity

| Test Status                 | Validity Code | # |
|-----------------------------|---------------|---|
| Acceptable Calibration Test | AC            | 1 |
| Total                       |               | 1 |

# Sequence VG Test Severity


- AES in precision warning alarm
- All other parameters in control
- Precision estimates not calculated as only 1 test was reported

# SEQUENCE VG INDUSTRY OPERATIONALLY VALID DATA




## AVERAGE ENGINE SLUDGE


LTMS Severity Analysis



LTMS Precision Analysis



CUSUM Severity Analysis



30MAR18:15:07

**Test Monitoring Center**

<http://astmtmc.cmu.edu>




A Program of ASTM International

# SEQUENCE VG INDUSTRY OPERATIONALLY VALID DATA




## AVERAGE ROCKER COVER SLUDGE


LTMS Severity Analysis



LTMS Precision Analysis



CUSUM Severity Analysis



**Test Monitoring Center**

<http://astmtmc.cmu.edu>





# SEQUENCE VG INDUSTRY OPERATIONALLY VALID DATA




## AVG. ENG. VARN. 3-PART APV + BAFFLES

### LTMIS Severity Analysis



### CUSUM Severity Analysis



**Test Monitoring Center**

<http://astmtmc.cmu.edu>




A Program of ASTM International

# SEQUENCE VG INDUSTRY OPERATIONALLY VALID DATA



## Avg Piston Skirt Rating



**Test Monitoring Center**


<http://astmtmc.cmu.edu>




A Program of ASTM International

## OIL SCREEN SLUDGE


## LTMS Severity Analysis




## LTMS Precision Analysis



## CUSUM Severity Analysis




# Sequence VG Precision Estimates




Precision estimates for Oct -18 not calculated  
as only one test reported this period

# Sequence VG Precision Estimates



Precision estimates for Oct -18 not calculated  
as only one test reported this period

# Sequence VG Precision Estimates



Precision estimates for Oct -18 not calculated  
as only one test reported this period

[Return to Table of Contents](#)

# Sequence VH

» October 2018

# Sequence VH Activity

| Test Status                            | Validity Code | #         |
|--|---------------|-----------|
| Acceptable Calibration Test            | AC            | 13        |
| Statistically Unacceptable Calibration | OC            | 2         |
| BOI-VGRA Matrix Test                   | NI            | 2         |
| Fuel Approval Test                     | AF            | 15        |
| <b>Total</b>                           |               | <b>32</b> |


# Sequence VH – Failing Tests

| Test Status          | #        |
|----------------------|----------|
| Level 3 Ei Alarm RAC | 2        |
| <b>Totals</b>        | <b>2</b> |

# Sequence VH Test Severity

- All parameters in control

## AVERAGE ENGINE SLUDGE




Test Monitoring Center


<http://astmtmc.cmu.edu>

## AVERAGE ROCKER COVER SLUDGE

Standard Deviation Units




Standard Deviation Units



## AVG. ENG. VARN. 50% RATING

Standard Deviation Units



LTMS Severity Analysis

EWMA  
OFF SCALE

EWMA Action Limit

EWMA Warning Limit


EWMA Warning Limit

EWMA Action Limit

COUNT IN COMPLETION DATE ORDER

CUSUM Severity Analysis

Standard Deviation Units



01 APR 17      01 OCT 17      01 APR 18

COUNT IN COMPLETION DATE ORDER


13 OCT 18:12:37

Test Monitoring Center

<http://astmtmc.cmu.edu>

## AVG PISTON SKIRT 50% RATING


Standard Deviation Units




Standard Deviation Units



# Sequence VH Precision Estimates



# Sequence VH Precision Estimates



[Return to Table of Contents](#)

# Sequence VIE

» October 2018

# Sequence VIE Activity

| Test Status   | Validity Code | #         |
|---|---------------|-----------|
| Acceptable Calibration Test                                   | AC            | 51        |
| Acceptable Industry Information Run (BOI-VGRA)                | NI            | 7         |
| Failed Statistically  | OC            | 4         |
| Operationally Invalid Calibration Test, Lab Judgement         | LC            | 2         |
| Operationally Invalid Calibration Test, Lab and TMC Judgement | RC            | 2         |
| Aborted Calibration Test                                      | XC            | 1         |
| <b>Total</b>  |               | <b>67</b> |

# Sequence VIE – Failed Tests

| Test Status        | Number of Tests |
|--------------------|-----------------|
| Mild FEI1          | 1               |
| FEI1 and FEI2 Mild | 1               |
| FEI1 Severe        | 1               |
| FEI1VI Alarm       | 1               |
| Total              | 4               |

# Sequence VIE – Lost Tests\*

| Test Status | Cause   | # |
|-------------|---|---|
| Aborted     | Fuel flow control                             | 1 |
| Invalid     | Exhaust backpressure out of spec              | 1 |
| Invalid     | Damaged oil filter                            | 1 |
| Invalid     | Coolant flow control stage 5                  | 1 |
| Invalid     | Micro Motion transmitter intermittent failure | 1 |
| Totals      |   | 5 |


\*Invalid and aborted tests

# Sequence VIE Test Severity


- FEI1 and FEI2 are in control

## FEI FINAL RESULT PHASE I

Standard Deviation Units




Standard Deviation Units




## FEI FINAL RESULT PHASE II


Standard Deviation Units



Standard Deviation Units



# Sequence VIE Precision Estimates



[Return to Table of Contents](#)

# Sequence VIF

» October 2018

# Sequence VIF Activity

| Test Status                                | Validity Code | #  |
|--|---------------|----|
| Acceptable Calibration Test                | AC            | 36 |
| Failed Statistically                       | OC            | 2  |
| Acceptable Industry Information Test (BOI) | NI            | 1  |
| Total                                      |               | 39 |



# Sequence VIF – Failed Tests

| Test Status   | Number of Tests |
|---------------|-----------------|
| Severe FEI1   | 1               |
| Vi Alarm FEI2 | 1               |
| <b>Total</b>  | <b>2</b>        |


# Sequence VIF Test Severity

- FEI1 and FEI2 are in control


# FEI FINAL RESULT PHASE I



## FEI FINAL RESULT PHASE II



# Sequence VIF Precision Estimates



[Return to Table of Contents](#)

# Sequence VIII

» October 2018

# Sequence VIII Activity

| Test Status                            | Validity Code | #  |
|--|---------------|----|
| Acceptable Calibration Test            | AC            | 6  |
| Operationally Invalid Calibration Test | LC            | 5  |
| Total                                  |               | 11 |

# Sequence VIII – Lost Tests\*

| Test Status | Cause                              | # |
|-------------|------------------------------------|---|
| Invalid     | Downtime exceeded procedural limit | 1 |
| Invalid     | High mechanical wear               | 4 |
| Totals      |                                    | 5 |

\*Invalid and aborted tests

# Sequence VIII Test Severity

- Bearing Weight Loss is in severity warning alarm (severe direction)
- Stripped Viscosity is in control



# SEQUENCE VIII INDUSTRY OPERATIONALLY VALID DATA



A Program of ASTM International

## FINAL BEARING WEIGHT LOSS

LTMS Severity Analysis



Test Monitoring Center

<http://astmtmc.cmu.edu>



A Program of ASTM International


# SEQUENCE VIII INDUSTRY OPERATIONALLY VALID DATA



Standard Deviation Units


STRIPPED VIS. @ 100 DEG C

LTMS Severity Analysis




Standard Deviation Units

LTMS Precision Analysis



Standard Deviation Units

CUSUM Severity Analysis




Test Monitoring Center

<http://astmtmc.cmu.edu>




A Program of ASTM International

# Sequence VIII Precision Estimates



# Sequence VIII Precision Estimates



[Return to Table of Contents](#)

# Sequence IX

» October 2018

# Sequence IX Activity

| Test Status                                 | Validity Code | #  |
|---|---------------|----|
| Acceptable Calibration Test                 | AC            | 42 |
| Alternate Fuel Test                         | NF            | 1  |
| Industry Information Test, BC Grade Pistons | NI            | 16 |
| Invalid Donated test, Reference oil 224     | LG            | 1  |
| Operationally Invalid, Laboratory Judgement | LC            | 5  |
| Statistically Unacceptable Calibration Test | OC            | 12 |
| Total                                       |               | 77 |

# Sequence IX – Failed Tests

| Test Status                  | Number of Tests |
|------------------------------|-----------------|
| Mild Average Pre-ignitions   | 6               |
| Severe Average Pre-ignitions | 6               |
| <b>Total</b>                 | <b>12</b>       |

# Sequence IX – Lost Tests\*

| Test Status | Cause                               | # |
|-------------|-------------------------------------|---|
| Invalid     | Cylinder 4 high activity            | 1 |
| Invalid     | Unable to obtain 4 valid iterations | 5 |
| Totals      |                                     | 6 |


\*Invalid and aborted tests

# Sequence IX Test Severity


- Average number of Pre-ignitions in severity warning alarm.

## AVERAGE NUMBER OF PREIGNITIONS FROM VALID ITERATIONS


Standard Deviation Units



Standard Deviation Units



# Sequence IX Precision Estimates



[Return to Table of Contents](#)

# Sequence X

» October 2018

# Sequence X Activity

| Test Status                                 | Validity Code | #  |
|---|---------------|----|
| Acceptable Calibration Test                 | AC            | 6  |
| Operationally Valid BOI-VGRA Test           | NI            | 8  |
| Aborted Calibration Test                    | XC            | 2  |
| Statistically Unacceptable Calibration Test | OC            | 1  |
| Total Number of Tests                       |               | 17 |

# Sequence X - Lost Tests\*

| Test Status | Cause                    | # |
|-------------|--------------------------|---|
| Aborted     | Turbocharger failure     | 1 |
| Aborted     | Oil loss during break-in | 1 |
| Totals      |                          | 2 |

\*Invalid and aborted tests


# Sequence X – Failed Tests

| Test Status      | Number of Tests |
|------------------|-----------------|
| Level 3 Ei Alarm | 1               |
| Total            | 1               |

# Sequence X Test Severity


- Average Chain Stretch % in control.

## END OF TEST CHAIN WEAR FINAL RESULT



# Sequence X Precision Estimates

CHST



[Return to Table of Contents](#)

# Information Letters

» October 2018

# Information Letters\*

| Test | Date     | IL   | Topic  |
|------|----------|------|--|
| IIIH | 20180406 | 18-2 | Revised updated Phosphorus measurement procedure   |
| IIIH | 20180731 | 18-3 | Added provisions for alternate cooling system, updated Tables 1 and 3 and Added dynamometer supplier information |
| VIE  | 20180410 | 18-1 | Added industry correction factors of +0.21 for FEI1 and +0.22 for FEI2   |
| VIE  | 20180723 | 18-2 | Added piston valve actuator to recommended hardware and corrected/updated supplier information footnotes         |
| VIE  | 20180823 | 18-3 | Corrected formulas in Annexes A15 and A16  |

\*Available from TMC Website

[Return to Table of Contents](#)

# Reference Oil Inventory

» Actions, Re-blends, Inventories  
and Estimated Life

# Reference Oil Re-blends

- TMC 222 and 224
  - < 1 year supply, supplier contacted, re-blend not available. 224 is available for introduction
- TMC 300-1
  - This re-blend is available, not introduced yet.
- TMC 434-3
  - This re-blend is available, tests being run to generate targets.

# Reference Oil Re-blends (cont)

- TMC 438-2
  - This re-blend is available, not yet introduced
- TMC 1009-1
  - This re-blend is available, not introduced yet.
- TMC 542-3
  - Little over a year supply remaining, supplier contacted for a re-blend.

# Reference Oil Inventory Estimated Life

| Oil   | Tests | Original Blend Amount (gallons) | Quantity Shipped in last 6 months | TMC Inventory (gallons) | Lab Inventory (gallons) | Estimated Life |
|-------|-------|---------------------------------|-----------------------------------|-------------------------|-------------------------|----------------|
| 220   | IX    | 1100                            | 145                               | 440                     | 50                      | 3 years        |
| 221   | IX    | 2120                            | 150                               | 1364                    | 60                      | 2.5+ years     |
| 222   | IX    | 1040                            | 145                               | 61                      | 60                      | <1 year        |
| 270   | X     | 1100                            | 15                                | 863                     | 30                      | 5 years        |
| 271   | X     | 980                             | 20                                | 804                     | 45                      | 5 years        |
| 300   | IVB   | 330                             | 0                                 | 7                       | 16                      | <1 year        |
| 300-1 | IVB   | 378                             | 32                                | 346                     | 24                      | 5 years        |
| 433-1 | IIIF  | 1045                            | 0                                 | 0                       | 8                       | <1 year        |
| 433-2 | IIIF  | 500                             | 32                                | 146                     | 32                      | 2+ years       |
| 434   | IIIG  | 550                             | 0                                 | <1                      | 12                      | <1 year        |

# Reference Oil Inventory Estimated Life

| Oil   | Tests      | Original Blend Amount (gallons) | Quantity Shipped in last 6 months | TMC Inventory (gallons) | Lab Inventory (gallons) | Estimated Life |
|-------|------------|---------------------------------|-----------------------------------|-------------------------|-------------------------|----------------|
| 434-1 | IIIG       | 660                             | 0                                 | 4                       | 20                      | 1.5 years      |
| 434-2 | IIIG, IIIH | 495                             | 18                                | 7                       | 28                      | <1 year        |
| 434-3 | IIIG, IIIH | 980                             | 50                                | 885                     | 44                      | 5+ years       |
| 435   | IIIG       | 550                             | 0                                 | 2                       | 4                       | <1 year        |
| 435-2 | IIIG       | 550                             | 18                                | 139                     | 32                      | 3+ years       |
| 436   | IIIH       | 1100                            | 25                                | 772                     | 36                      | 5+ years       |
| 438   | IIIG       | 990                             | 0                                 | 16                      | 28                      | 1.5 years      |
| 438-1 | IIIH       | 605                             | 16                                | 26                      | 36                      | <1 year        |
| 438-2 | IIIH       | 540                             | 0                                 | 540                     | 0                       | 5 years        |
| 542-2 | VIE        | 1000                            | 0                                 | 0                       | 6                       | <1 year        |
| 542-3 | VIE        | 997                             | 190                               | 370                     | 136                     | 1+Years        |

# Reference Oil Inventory Estimated Life

| Oil    | Tests         | Original Blend Amount (gallons) | Quantity Shipped in last 6 months | TMC Inventory (gallons) | Lab Inventory (gallons) | Estimated Life |
|--------|---------------|---------------------------------|-----------------------------------|-------------------------|-------------------------|----------------|
| 543    | VIF           | 1100                            | 105                               | 657                     | 48                      | 3+ Years       |
| 544    | VIE           | 897                             | 44                                | 277                     | 78                      | 2+ years       |
| 704-1  | VIII          | 897                             | 14                                | 89                      | 10                      | 5+ years       |
| 940    | VG, VH        | 560                             | 42                                | 157                     | 24                      | 2+ years       |
| 1006-2 | IVA, VG, VIII | 5500                            | 320                               | 1024                    | 32                      | 2 years        |
| 1009   | VG, VH, VIII  | 1100                            | 0                                 | 34                      | 6                       | <1 year        |
| 1009-1 | VG, VH, VIII  | 1100                            | 9                                 | 1094                    | 15                      | 5 years        |
| 1010-1 | VIE           | 1760                            | 218                               | 583                     | 108                     | 2 years        |
| 1011   | IVB/VH/VIF/X  | 1100                            | 183                               | 495                     | 148                     | 2 years        |
| 1012   | IVB           | 2200                            | 64                                | 2001                    | 16                      | 5+ years       |

[Return to Table of Contents](#)

# LTMS Deviations

» April 1, 2018 -  
September 30, 2018

# LTMS Deviations

- No LTMS Deviations this period

# LTMS Deviations

## Historical Count of PCEO LTMS Deviations

| Test | LTMS Deviations |
|------|-----------------|
| IIIF | 6               |
| IIIG | 6               |
| IIIH | 0               |
| IVA  | 7               |
| VG   | 8               |
| VID  | 3               |
| VIE  | 0               |
| VIF  | 0               |
| VIII | 3               |
| IX   | 0               |
| X    | 0               |

[Return to Table of Contents](#)

# Quality Index Deviations

» April 1, 2018 -  
September 30, 2018

# Quality Index Deviations

- Two Quality Index Deviations this Report Period.
  - VH – Exhaust backpressure (Lab G)
  - VH – Engine oil inlet and coolant outlet temperatures (Lab A)

# Quality Index Deviations

## Historical Count of PCEO Quality Index Deviations

| Test | Quality Index Deviations |
|------|--------------------------|
| IIIF | 28                       |
| IIIG | 16                       |
| IIIH | 5                        |
| IVA  | 30                       |
| VG   | 46                       |
| VH   | 2                        |
| IX   | 1                        |
| X    | 2                        |

[Return to Table of Contents](#)

# TMC Laboratory Visits

» April 1, 2018 -  
September 30, 2018

# TMC Lab Visits

| Test | Number of Labs Visited |
|------|------------------------|
| IIIH | 3                      |
| VH   | 2                      |
| VIE  | 3                      |
| VIII | 1                      |
| X    | 1                      |

# Lab Visit Issues

- VIII

- Crankcase pressure not located properly.

- IIIH

- A minimum of 10 lengths of straight pipe not maintained downstream of J-Tec meter.

Labs have notified the TMC that these items were corrected or were corrected during the visit

[Return to Table of Contents](#)

# Test Area Timelines

» April 1, 2018 -  
September 30, 2018

# Test Area Timeline Additions\*

| Test | Date     | Topic  | IL   |
|------|----------|--|------|
| IIIH | 20180406 | Revised updated Phosphorus measurement procedure   | 18-2 |
| IIIH | 20180731 | Added provisions for alternate cooling system, updated Tables 1 and 3 and Added dynamometer supplier information | 18-3 |
| IVB  | 20180510 | LTMS Implemented for AVLI Parameter  | N/A  |
| VIE  | 20180410 | Added industry correction factors of +0.21 for FEI1 and +0.22 for FEI2   | 18-1 |
| VIE  | 20180723 | Added piston valve actuator to recommended hardware and corrected/updated supplier information footnotes         | 18-2 |
| VIE  | 20180823 | Corrected formulas in Annexes A15 and A16  | 18-3 |

\*As of 09/30/2018

[Return to Table of Contents](#)

# Rating Workshop Data


» 2018 Light Duty Workshop

# Rating Workshop Data

- ▶ Summary of Precision Data From Light Duty Rating workshops:
  - VG Average Piston and Average Engine Varnish.
  - IIIG WPD
  - IIIH WPD


# Sequence VG Precision-Rating Workshop Data

## Workshop Data for VG/VH Varnish



# Sequence IIIG Precision – Rating Workshop Data


## Comparison of Workshop Pooled Standard Deviations with Industry Pooled Standard Deviations



[Return to Table of Contents](#)

# Sequence IIIH Precision – Rating Workshop Data

## Comparison of Workshop Pooled Standard Deviations with Industry Pooled Standard Deviations



[Return to Table of Contents](#)

# Miscellaneous Information

- ▶ Available on TMC Website:
  - Live Reference Test Data Bases
  - Surveillance Panel Meeting Minutes
  - Test Area Alarm Logs
  - Complete Test Area Timelines
  - LTMS Manual
- ▶ [www.astmtmc.cmu.edu](http://www.astmtmc.cmu.edu)

[Return to Table of Contents](#)

*Test Monitoring Center*  
<http://astmtmc.cmu.edu>



A Program of ASTM International



**A Program of ASTM International**