

**Test Monitoring Center** 

203 Armstrong Drive, Freeport, PA 16229, USA

www.astmtmc.org 412-365-1000

## **CERTIFICATE OF ANALYSIS**

**TMC Product ID:** Product Purpose: Product Description: TMC Batch Number: Certificate Issue Date: JFA-11 Reference Fluid A for ASTM D5001 Jet Fuel 20221116A 20230501

Product Appearance: Bright and clear liquid, nearly water white

<u>Properties</u>			
ASTM D93	Flash Point	98.5	°C
ASTM D4052	Digital Density at 15°C	0.7855	g/mL

## Aviation Turbine Fuel Lubricity by BOCLE Reference Targets ASTM D5001

	Wear Scar Diameter		
Fluid Name	Target, mm	Lower Acceptance, mm	Upper Acceptance, mm
JFA 11 High Lubricity Reference (Fluid A Lot 11)	0.577	0.537	0.617

Store at ambient temperature not exceeding 10 – 40°C (50 - 104°F). Do not refrigerate.

The jet fuel lubricity reference fluids are procured under the direction of ASTM subcommittee D02.J0.04. When stored under the recommended conditions, the committee has not advised that these products expire but the end user should always use their best scientific judgment.

Brittany J. Pfleegor Supervisor, Analytical Testing ASTM Test Monitoring Center 412-365-1013 bjp@astmtmc.org