

## **Test Monitoring Center**

203 Armstrong Drive, Freeport, PA 16229, USA

www.astmtmc.org 412-365-1000

## **CERTIFICATE OF ANALYSIS**

TMC Product ID: JFB-12

Product Purpose: Reference Fluid B for ASTM D5001

Product Description: Jet Fuel TMC Batch Number: 20250311A Certificate Issue Date: 20250528

Product Appearance: Bright and clear liquid, nearly water white

<u>Properties</u>

ASTM D93 Flash Point 98.5 °C ASTM D4052 Digital Density at 15°C 0.7856 g/mL

## Aviation Turbine Fuel Lubricity by BOCLE Reference Targets ASTM D5001

	Wear Scar Diameter		
Fluid Name	Target, mm	Lower Acceptance, mm	Upper Acceptance, mm
JFB 12 Low Lubricity Reference (Fluid B Lot 12)	0.803	0.723	0.883

Store at ambient temperature not exceeding  $10 - 40^{\circ}$ C (50 -  $104^{\circ}$ F). Do not refrigerate.

The jet fuel lubricity reference fluids are procured under the direction of ASTM subcommittee D02.J0.04. When stored under the recommended conditions, the committee has not advised that these products expire but the end user should always use their best scientific judgment.

Brittany J. Pfleegor Supervisor, Analytical Testing ASTM Test Monitoring Center 412-365-1013 bjp@astmtmc.org