## EXXONMOBIL TECHNOLOGY & ENGINEERING CO 1545 ROUTE 22 EAST CLINTON TOWNSHIP 08801, ANNANDALE United States



Print Date: 10-08-2025 15:57

Page 1 of 2

Attention of : Mr. P. Rubas

**Analysis Report** 

Report number : 13051/00076775.1/L/25 Submitted date : 10-07-2025

Sample submitted at : Saybolt LP, Deer Park

Report Date : 10-08-2025 Date received : 10-07-2025

Date of issue : 10-08-2025 Date completed : 10-08-2025

Sample object : ExxonMobil - Annandale Sample number : 18506970

Sample type : Submitted Sample submitted as : Gasoline

Marked : 25-35529/00 (HF2003-2H2025) VIE Gasoline

NAME	METHOD	UNIT	RESULT
API Gravity	ASTM D4052	°API	58.8
Distillation	ASTM D86		
Initial boiling point		°F	86.8
5% Evaporated		°F	112.7
10% Evaporated		°F	125.8
20% Evaporated		°F	144.5
30% Evaporated		°F	167.1
40% Evaporated		°F	195.3
50% Evaporated		°F	218.8
60% Evaporated		°F	230.6
70% Evaporated		°F	240.7
80% Evaporated		°F	257.8
90% Evaporated		°F	312.8
95% Evaporated		°F	336.7
Final boiling point		°F	395.3
Recovery		vol %	97.6
Residue		vol %	1.1
Loss		vol %	1.3
Evaporated at 200 °F		vol %	41.6
Evaporated at 300 °F		vol %	88.4
Heat Of Combustion, Net	ASTM D3338	Btu/lb	18636
Hydrocarbon Type FIA	ASTM D1319		
Aromatics		vol %	16.0
Olefins		vol %	0.9
Saturates		vol %	83.1
Sulfur	ASTM D5453	mg/kg	2.2
Vapor Pressure	ASTM D5191		

All results in this report refer to sample(s) tested as taken or submitted like specified in this analysis report. All tests are conducted according to the latest version of the methods, unless stated otherwise. Measuring results have an uncertainty as quantified by the precision parameters of each test method. Precision parameters may deviate if the sample matrix is beyond the scope of the test method and / or result is out of stated range. For the interpretation of results, users should refer to ASTM D3244, IP367, ISO 4259 or GOST 33701. This report shall not be partially reproduced without written permission of SAYBOLT.

Saybolt expressly disclaims any representation in this report, whether express or implied, as to the origin of the crude or refined product identified herein. Any designation as to origin is made solely by the party requesting the analysis. Saybolt has not verified the tested parameters against any supplied specification for purposes of establishing origin. Further, any certification provided is solely as to the physical and chemical properties of the sample identified in this report.

## EXXONMOBIL TECHNOLOGY & ENGINEERING CO **1545 ROUTE 22 EAST CLINTON TOWNSHIP** 08801, ANNANDALE **United States**



Print Date: 10-08-2025 15:57

Page 2 of 2

Attention of : Mr. P. Rubas

**Analysis Report** 

Report number : 13051/00076775.1/L/25 Submitted date : 10-07-2025

Sample submitted at : Saybolt LP, Deer Park

Report Date : 10-08-2025 : 10-07-2025 Date received Date of issue : 10-08-2025 Date completed : 10-08-2025 Sample object : ExxonMobil - Annandale Sample number : 18506970

Sample type : Submitted Sample submitted as : Gasoline

Marked : 25-35529/00 (HF2003-2H2025) VIE Gasoline

NAME	METHOD	UNIT	RESULT
Vapor Pressure, EPA Eq.		psi@100F	8.90
Vapor Pressure, ASTM Eq.		psi@100F	8.79

Signed by: Sandra Kaluza - Laboratory Coordinator I Issued by: Saybolt LP

Place and date of issue: Deer Park - 10-08-2025

All results in this report refer to sample(s) tested as taken or submitted like specified in this analysis report. All tests are conducted according to the latest version of the methods, unless stated otherwise. Measuring results have an uncertainty as quantified by the precision parameters of each test method. Precision parameters may deviate if the sample matrix is beyond the scope of the test method and / or result is out of stated range. For the interpretation of results, users should refer to ASTM D3244, IP367, ISO 4259 or GOST 33701. This report shall not be partially reproduced without written permission of SAYBOLT.

Saybolt expressly disclaims any representation in this report, whether express or implied, as to the origin of the crude or refined product identified herein. Any designation as to origin is made solely by the party requesting the analysis. Saybolt has not verified the tested parameters against any supplied specification for purposes of establishing origin. Further, any certification provided is solely as to the physical and chemical properties of the sample identified in this report.